

# Chemistry, Bonds with Passion

Aik Moh Group is an leading SEA chemical distributor and service provider. We offer comprehensive range of chemicals and chemical-related services including toll blending, repacking and other logistics support.

Aik Moh Paints & Chemicals Pte Ltd

20 Tuas Street  
Singapore 638457  
Email: [Enquiry@Aikmoh.com.sg](mailto:Enquiry@Aikmoh.com.sg)

## Aik Moh Group

### Hydrocarbon Fluids

### ULTRE Series



**AIK MOH**  
PAINTS & CHEMICALS

Hydrocarbon Fluids ULTRE Special Blend		Aromatic %	Distillation Range °C	Flash Point °C	Density at 15.6 °C	Aniline Point °C	CAS Number
Iso-Paraffins	ULTRE 3340S	< 0.025	150 - 196	min 40	0.75	81	64742-48-9 / 64742-47-8
	ULTRE 3350J	< 0.025	170 - 215	min 54	0.77	81	64742-48-9 / 64742-47-8
	ULTRE 3360S	< 0.025	179 - 218	min 60	0.77	81	64742-48-9 / 64742-47-8
	ULTRE 3380J	< 0.025	205 - 265	min 80	0.80	86	64742-48-9 / 64742-47-8
Normal-Paraffins	ULTRE 1100N	< 0.01	85 - 100	< -7	0.71	68	64742-49-0
	ULTRE 3307	< 0.01	94 - 128	< 2	0.71	62	64742-49-0
	ULTRE 3120	< 0.05	240 - 255	120	0.76	90	64742-47-8
	ULTRE 3130G	< 0.01	274 - 305	130	0.78	92	64742-46-7
	ULTRE 3160G	< 0.01	310 - 355	160	0.80	102	64742-46-7

#### Applications :

- Aluminium rolling oils (ULTRE 3380J, Conventional D80)
- Concrete mould release agents (D-series below Flash Point 60 °C is preferred)
- Consumer products: aerosols, polishes, cleaners (ULTRE 3350J/3340S/3380J)
- Crop protection products (Aromatics Fluids, Higher D-series, ULTRE Series except low flash points grades)
- Defoamers (D40/D60 series)
- Drilling muds (Conventional D80 series)
- Heat transfer fluids (ULTRE 3130G/3160G)
- Heating and lighter fluids (ULTRE Series with Extremely Low Smoke/Soot)
- Institutional cleaning products (ULTRE Series with Optimal Solvency and Drying Rate for precision and auto metal parts processing)
- Metal working (ALL applicable, especially for EDM, AL Rolling Oil and Metal Stamping Oil Formulations)
- Mining solvents (D80, ULTRE 3380J, or Blended Aromatics)
- Paints, coatings and inks (All with Flash Point below 80 °C are applicable for wood and low odour coating formulations)
- Personal Care and Cosmetics (D60 and ULTRE 3360S, D80 and ULTRE 3380J)
- Polymer extender oils (D80 and above)
- Process diluents (D80 and above)
- Sealants (Hexane/IsoHex/Heptane/Ultre 3307)
- Water treatment products (D80, D110, D130, D120)

© 2018 Aik Moh Paints & Chemicals Pte Ltd (Singapore). To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute and/or photocopy this copyright document only if unaltered and complete, including all of its headers, footers, disclaimers and other information. We do not represent, warrant or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement or any product or process and we expressly disclaim any contrary implement. Value shown in the table represent the typical values and do not constitute specification limits